

# AXIS 4K ULTRAHD IR PTZ

INFRARED HARDWARE & STREAMING PACKAGE



**DESIGN • BUILD • INSTALL • STREAM**

ANY SCREEN. ANY DEVICE.  
STREAMING SERVICES REDEFINED.



## HARDWARE ARRIVES TESTED AND READY FOR INSTALLATION

Your hardware package is **pre-built, pre-configured & tested** prior to shipping! Rest easy knowing that your HDonTap coordinator has done the legwork, and your equipment is ready for an **easy installation**. HDonTap representatives are available for assistance during your installation and setup, ensuring a **quick and easy process**.

## RELY ON OUR SUPPORT AND EXPERTISE

HDonTap Support is just a click or call away during your installation and beyond. In addition to **live support**, our **online knowledge base** is available whenever you are. Ensure you are capitalizing on your investment with our **post-integration live stream review** and get helpful marketing tips to realize the full potential of your live cam.

## MARKETING TOOLS THAT INCREASE YOUR VISIBILITY

Stream your live cam with HDonTap and enjoy **additional savings**! In addition to standard streaming features such as **watermark overlay** and **video ad inserts**, HDonTap's proprietary streaming service includes **real-time snapshots**, **anti-stream hijacking security**, **automated time-lapse creation** and much more!



## ENGAGE YOUR AUDIENCE WITH CRYSTAL-CLEAR HD LIVE STREAMS

HDonTap's Axis 4K UltraHD IR PTZ Package is a non-China based IR PTZ webcam streaming solution. The package includes a 4K UltraHD outdoor PTZ camera with Integrated Infrared and arrives with a PoE power adapter and wall mount bracket for an easy self-installation. Enjoy 4,000 viewer hours/month of HD live streaming as well as HDonTap's time-lapse service with enhanced preset tour - generate time-lapse clips automatically while simultaneously live streaming!

**This package arrives pre-built, configured and tested** - the perfect solution for live webcam streaming and time-lapse video services!

**Get started today by calling 858.481.4096 or visiting [hdontap.com](http://hdontap.com)**

## PACKAGE INCLUDES:

### 4K ULTRAHD IR PTZ CAMERA

- Axis Q6318-LE Pan/Tilt/Zoom Camera
- 3840x2160 4K UltraHD Resolution
- 31x Optical Zoom & Laser Focus
- Integrated IR Illumination
- POE Injector & 100' Cat5e Outdoor Rated Cable Included
- Wall / Pole Mount Included

### 1 YEAR LITE STREAMING PLAN

- Unlimited Concurrent Viewers on Any Device (Desktop or Mobile)
- 4,000 Viewer Hours / Month
- Branded Live Stream Player w/ Social Media Sharing Integration
- Automated Time-Lapse Clips
- Email, Chat & Phone Support
- Stream Stats and Analytics
- HDonTap Web Portal Access
- Up to 2 Webcams

HARDWARE: \$3,878 MSRP

STREAMING: \$3,348 MSRP

**PACKAGE PRICE: \$4,999**

SAVINGS: \$2,227

# AXIS Q6318-LE PTZ Camera

4K UHD PTZ with quick-zoom and laser focus

AXIS Q6318-LE offers superior 4K UHD resolution. It features IR illumination and day/night functionality for surveillance in pitch darkness. With a built-in laser, 31x optical zoom, you can easily follow fast-moving objects and quick-zoom makes it move from wide to tele view in just 1 second. This high-speed PTZ camera includes orientation aid and autotracking 2 with click and track functionality. AXIS Object Analytics lets you detect and classify humans and vehicles. Furthermore, it includes a Trusted Platform Module (TPM) that's FIPS 140-2 level 2 certified.

- > 1/2" sensor with 31x optical zoom
- > IR illumination, D/N functionality, Lightfinder 2.0
- > Laser focus for precise focus
- > AXIS Object Analytics, autotracking 2
- > TPM, FIPS 140-2 level 2 certified



# AXIS Q6318-LE PTZ Camera

<b>Variants</b>	AXIS Q6318-LE 50 Hz AXIS Q6318-LE 60 Hz	<b>Event conditions</b>	Device status: above operating temperature, above or below operating temperature, below operating temperature, fan failure, IP address removed, network lost, new IP address, shock detected, storage failure, system ready, within operating temperature Edge storage: recording ongoing, storage disruption I/O: manual trigger, virtual input MQTT subscribe PTZ: PTZ malfunctioning, PTZ movement, PTZ preset position reached, PTZ ready Scheduled and recurring: scheduled event Video: average bitrate degradation, day-night mode, live stream open
<b>Camera</b>		<b>Event actions</b>	Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share and email Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS, TCP and SNMP trap PTZ: PTZ preset, start/stop guard tour Overlay text, day/night mode WDR mode IR illumination MQTT publish
<b>Image sensor</b>	1/2" progressive scan CMOS	<b>Analytics</b>	
<b>Lens</b>	Focal length: 6.91 – 214.64 mm, F1.36 – F4.6 Horizontal field of view: 58.5°– 2.3° Vertical field of view: 34.9°– 1.4° Laser focus, autofocus, P-iris Zoom speed: <1 sec between any zoom value	<b>AXIS Object Analytics</b>	Object classes: humans, vehicles Scenarios: line crossing, object in area, crossline counting, time in area Up to 10 scenarios Metadata visualized with color-coded bounding boxes Polygon include/exclude areas Perspective configuration ONVIF Motion Alarm event
<b>Day and night</b>	Automatically removable infrared-cut filter	<b>Metadata</b>	<b>Object data:</b> Classes: humans, faces, vehicles (types: cars, buses, trucks, bikes), license plates Confidence, position <b>Event data:</b> Producer reference, scenarios, trigger conditions
<b>Minimum illumination</b>	Color: 0.11 lux at 30 IRE, F1.36 B/W: 0.001 lux at 30 IRE, F1.36, 0 lux with IR illumination on Color: 0.25 lux at 50 IRE, F1.36 B/W: 0.009 lux at 50 IRE, F1.36, 0 lux with IR illumination on	<b>Applications</b>	<b>Included</b> AXIS Object Analytics, AXIS Video Motion Detection, AXIS Motion Guard, AXIS Fence Guard, AXIS Loitering Guard, AXIS OSDI Zone, Orientation Aid PTZ, advanced gatekeeper, autotracking 2 Support for AXIS Camera Application Platform enabling installation of third-party applications, see <a href="https://axis.com/ocap">axis.com/ocap</a>
<b>Shutter speed</b>	1/8500 s to 1/5 s with 50 Hz 1/8500 s to 1/5 s with 60 Hz	<b>Approvals</b>	
<b>Pan/Tilt/Zoom</b>	Pan: 360° endless, 0.05°– 550°/s Tilt: +20 to -90°, 0.05°– 500°/s Zoom: 31x optical, 12x digital, Total 372x zoom Quick-zoom, nadir flip, 300 preset positions, tour recording (max 10, max duration 16 minutes each), guard tour (max 100), control queue, on-screen directional indicator, set new pan 0°, adjustable zoom speed, speed dry	<b>EMC</b>	EN 55032 Class A, EN 55035, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, CISPR 35, EAC, EN 50121-4 <b>Australia/New Zealand:</b> RCM AS/NZS CISPR 32 Class A <b>Canada:</b> ICES-3(A)/NMB-3(A) <b>Japan:</b> VCCI Class A <b>Korea:</b> KS C 9832 Class A, KS C 9835 <b>USA:</b> FCC Part 15 Subpart B Class A <b>Railway:</b> IEC 62236-4
<b>System on chip (SoC)</b>		<b>Safety</b>	IEC/EN/UL 62368-1 ed. 3, CAN/CSA C22.2 No. 62368-1 ed. 3, IEC/EN 62471 risk group 2, IEC 60825-1 Class 1, IS 13252
<b>Model</b>	ARTPEC-7	<b>Environment</b>	IEC/EN 62262 IK10, IEC/EN 60529 IP66, IEC/EN 60529 IP67, NEMA 250, Type 4X, NEMA TS 2 (2.2.7–2.2.9), IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78, ISO 21207 (Method B)
<b>Memory</b>	2048 MB RAM, 512 MB Flash	<b>Network</b>	NIST SP500-267
<b>Compute capabilities</b>	Machine learning processing unit (MLPU)	<b>Cybersecurity</b>	ETSI EN 303 645
<b>Video</b>		<b>Cybersecurity</b>	
<b>Video compression</b>	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles H.265 (MPEG-H Part 2/HEVC) Main Profile Motion JPEG	<b>Edge security</b>	<b>Software:</b> Signed firmware, brute force delay protection, digest authentication and OAuth 2.0 RFC6749 OpenID Authorization Code Flow for centralized ADFS account management, password protection, AES-XTS-Plain64 256bit SD card encryption <b>Hardware:</b> Axis Edge Vault cybersecurity platform TPM 2.0 (CC EAL4+, FIPS 140-2 Level 2), secure element (CC EAL 6+), Axis device ID, secure keystore, signed video, secure boot
<b>Resolution</b>	3840x2160 4K UHD	<b>Network security</b>	IEEE 802.1X (EAP-TLS, PEAP-MSCHAPv2) <sup>a</sup> , IEEE 802.1AE (MACsec PSK/EAP-TLS), IEEE 802.1AR, HTTPS/HSTS <sup>a</sup> , TLS v1.2/v1.3 <sup>a</sup> , Network Time Security (NTS), X.509 Certificate PKI, host-based firewall
<b>Frame rate</b>	Up to 25/30 fps (50/60 Hz) in all resolutions		
<b>Video streaming</b>	Multiple, individually configurable streams in H.264, H.265 and Motion JPEG Axis Zipstream technology in H.264 and H.265 Controllable frame rate and bandwidth VBR/ABR/MBR H.264/H.265 Low latency mode Video streaming indicator		
<b>Image settings</b>	Compression, color, brightness, sharpness, white balance, exposure control, exposure zones, image freeze on PTZ, scene profiles, rotation, electronic image stabilization (EIS), defogging Contrast, local contrast, autofocus, Forensic WDR: Up to 120 dB depending on scene, 32 individual polygon privacy masks including mosaic privacy mask		
<b>Network</b>			
<b>Security</b>	multi-level user, IP address filtering, HTTPS <sup>a</sup> encryption, IEEE 802.1x (EAP-TLS) <sup>a</sup> , network access control, user access log, centralized certificate management		
<b>Network protocols</b>	IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTPS <sup>a</sup> , HTTP/2, TLS <sup>a</sup> , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP <sup>®</sup> , SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, NTS, RTSP, RTCP, RTP, SRTP/RTSPS, TCP, UDP, IGMPv1/v2/v3, DHCPv4/v6, ARP, SSH, NTCIP, LLDP, CDP, MQTT v3.1.1, Secure syslog (RFC 3164/5424, UDP/TCP/TLS), Link-Local address (ZeroConf)		
<b>System integration</b>			
<b>Application Programming Interface</b>	Open API for software integration, including VAPIX <sup>®</sup> and AXIS Camera Application Platform; specifications at <a href="https://axis.com">axis.com</a> One-Click Cloud Connection ONVIF <sup>®</sup> Profile G, ONVIF <sup>®</sup> Profile M, ONVIF <sup>®</sup> Profile S, and ONVIF <sup>®</sup> Profile T, specification at <a href="https://onvif.org">onvif.org</a>		
<b>Onscreen controls</b>	IR illumination Quick-zoom Enable/disable all privacy masks Speed dry		

<b>Documentation</b>	<p><i>AXIS OS Hardening Guide</i>  <i>Axis Vulnerability Management Policy</i>  <i>Axis Security Development Model</i>            AXIS OS Software Bill of Material (SBOM)            To download documents, go to <a href="https://axis.com/support/cybersecurity/resources">axis.com/support/cybersecurity/resources</a>            To read more about Axis cybersecurity support, go to <a href="https://axis.com/cybersecurity">axis.com/cybersecurity</a></p>
<b>General</b>	
<b>Casing</b>	<p>IP66-, IP67, NEMA 4X- and IK10-rated            Color: white NCS S 1002-B            Repaintable metal casing (aluminum), hard coated Polycarbonate (PC) clear dome with Sharpdome technology</p>
<b>Sustainability</b>	PVC free
<b>Power</b>	<p>Axis High PoE 60 W SFP midspan 1-port:            100–240 V AC, max 1.5 A            IEEE802.3bt Type 3 Class 6            Possibility to optimize power consumption of camera:            Full power: typical 15 W (no IR), max 51 W            Low power: typical 15 W (no IR), max 30 W. With IR: 44 W</p>
<b>Connectors</b>	<p>RJ45 10BASE-T/100BASE-TX/1000BASE-T            RJ45 Push-pull Connector (IP66)</p>
<b>IR illumination</b>	<p>OptimizedIR with power-efficient, long-life 850 nm IR LEDs            Range of reach 200 m (656 ft) or more depending on the scene</p>
<b>Storage</b>	<p>Support for SD/SDHC/SDXC card            Support for SD card encryption (AES-XTS-Plain64 256bit)            Support for recording to network-attached storage (NAS)            For SD card and NAS recommendations see <a href="https://axis.com">axis.com</a></p>
<b>Operating conditions</b>	<p>Full power: -50 °C to 50 °C (-58 °F to 122 °F)            Low power: -5 °C to 50 °C (23 °F to 122 °F)</p>

	<p>Maximum temperature according to NEMA TS 2 (2.2.7): 74 °C (165 °F)            Arctic temperature control: start-up as low as -40 °C (-40 °F)            Humidity: 10–100% RH (condensing)</p>
<b>Storage conditions</b>	<p>-40 °C to 65 °C (-40 °F to 149 °F)            Humidity: 5–95% RH (non-condensing)</p>
<b>Dimensions</b>	<p>Height: 261 mm (10.3 in)            With weather shield: ø 239 mm (9.4 in)            Without weather shield: ø 192 mm (7.6 in)</p>
<b>Weight</b>	4 800 g (10.6 lb)
<b>Included accessories</b>	<p>Installation guide, Windows® decoder 1-user license, 60 W Midspan (including power cable), IP66 rated network connector, repaint template, paint paper</p>
<b>Optional accessories</b>	<p>AXIS T91/T94 Mounting Accessories            AXIS T8415 Wireless Installation Tool            AXIS Surveillance Cards            For more accessories, see <a href="https://axis.com">axis.com</a></p>
<b>Video management software</b>	<p>AXIS Companion, AXIS Camera Station, video management software from Axis Application Development Partners available at <a href="https://axis.com/vms">axis.com/vms</a></p>
<b>Languages</b>	<p>English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Polish, Traditional Chinese, Dutch, Czech, Swedish, Finnish, Turkish, Thai, Vietnamese</p>
<b>Warranty</b>	5-year warranty, see <a href="https://axis.com/warranty">axis.com/warranty</a>

- a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. ([openssl.org](https://openssl.org)), and cryptographic software written by Eric Young ([eyay@cryptsoft.com](mailto:eyay@cryptsoft.com)).